LM SERIES / PRODUCT OVERVIEW

LM Narrow Glass-Face

Linear architectural LED wall washers



LM-2632

MODEL & POWER

Model	Power	Housing weight
LM-2632	18 W-72 W	2.1 kg

Confirm the required wattage when ordering.

LM SERIES / TECHNICAL DATA

Technical specifications

LM Narrow Glass-Face

Parameter	Specification
Input voltage	24 V DC
Ingress protection	IP67
Impact resistance	IK10
Maximum efficacy	85 lm/W
Beam angles (reference)	11° / 17° / 29° / 58° / 14° × 38° / 18° × 37°
Light color	White / RGB / RGBW / Single color
White CCT (factory-set)	2200 / 2700 / 3000 / 3500 / 4000 / 5000 / 6000 K Other factory-set white CCT options within 2000-6500 K
Control	DMX512 / On/off / DALI
Operating temperature	-50 to +60 °C
Housing material	6063 aluminum alloy
Optical cover	8 mm tempered extra-clear glass
Warranty	5 years

Custom beam angles are available on request.

LM SERIES / MECHANICAL DATA

Dimensions & mounting

LM Narrow Glass-Face

LM-2632

Body dimensions (L × W × H)	**1000 × 26.6 × 32 mm**
Installed height	**56.9 mm**

END VIEW

